



The relief-before-check cartridge is a CavitySaver™ (multi-function) valve incorporating a direct-acting relief tee'd in before a check function. When the pressure at the inlet (port 2) reaches the relief valve setting, the valve starts to open to tank (port 3), throttling flow to limit the pressure rise. The check valve flow is from the inlet (port 2) to the system port (port 1). These valves are smooth and quiet, essentially zero leak, dirt tolerant, immune to silting and are very fast.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	4 gpm
Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at Reseat	5 drops/min.
Check Cracking Pressure	25 psi
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	6
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	Polyurethane: 990011002
Seal kit - Cartridge	Viton: 990011006

CONFIGURATION OPTIONS

Model Code Example: HRDALAN

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	Standard Material/Coating
C Tamper Resistant - Factory Set	D 200 - 700 psi (14 - 50 bar), 400 psi (28 bar) Standard Setting	V Viton	/AP Stainless Steel, Passivated
K Handknob	W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting		